

FLEXCONSOLE



APPLICATION

For heating and chilled water (cooling) installations.

A multi function product which provides all the essential requirements for a sealed chilled or heated water system i.e. automatic expansion control, pressurisation, de-aeration and make-up.

Characteristics:

Pressureless vessel without automat.

Replaceable bladder.

Automatically maintains volumetric control during heating or cooling cycles along with automatic make-up.

Total air removal, even when the system is in a state of equilibrium, unique turbo de-aeration facility provides continuous de-aeration when required.

TECHNICAL DATA

Material: steel ASTM/ISO: A181 class 60 / S235JRG2

Painting: Red (RAL 3002) epoxy powder coating.

Max working temperature: 70 °C.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Max working temperature at outlet: 90 °C.

Max design temperature: 120°C.

APPROVALS

CE 0045 in according with PED 97/23/EC.

Codice	Nome	Peso	Numero di pezzi
27910	3/4"	1.14	1
27996	3/4"	1.7	1
27989	3/4" bianca	1.14	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com