

FLAMCOVENT CLEAN SMART PN10



TECHNICAL SPECIFICATIONS

With flanged connection according to EN 1092-1 PN16. Maximum working pressure: 10 bar. Models with a Maximum working pressure of 25 bar are available upon request. Suitable for systems with a maximum flow temperature of 120 °C. Suitable for glycol solutions of up to 50%. In accordance with Pressure Equipment Directive 2014/68/EU.

DN	Capacity [L]	Ø [mm]	A [mm]	B [mm]	C [mm]	D [mm]	Kv * [m ³ /h] (delta P = 1 bar)
50	8	60,3	603	350	333	175	93
65	10	76,1	603	350	333	175	140
80	33	88,9	795	470	435	270	209
100	33	114,3	795	470	435	270	311
125	78	139,7	967	635	515	360	459
150	78	168,3	967	635	515	360	675
200	158	219,1	1280	774	705	450	1340
250	370	273,1	1620	990	892	600	1952
300	415	323,9	1784	1006	1032	600	2830
350	840	355,6	2028	1214	1109	800	4084
400	927	406,4	2201	1220	1252	800	5866
500	1768	508	2628	1580	1470	1000	8387

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

DN	Capacity [L]	Ø [mm]	A [mm]	B [mm]	C [mm]	D [mm]	Kv * [m3/h] (delta P = 1 bar)
600	3056	610	3124	1870	1757	1200	11939

Codice	Nome	Peso	Numero di pezzi
31041	DN 50	16	1
31042	DN 65	17	1
31044	DN 80	28	1
31045	DN 100	32	1
31046	DN 125	55	1
31047	DN 150	63	1
31048	DN 200	86	1
31049	DN 250	165	1
31051	DN 350	350	1
31052	DN 400	385	1
31054	DN 600	1075	1
31050	DN 300	200	1
31053	DN 500	745	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com