

FLAMCO CLEAN F PN10 - prosystemitalia.com

FLAMCO CLEAN F PN10



APPLICATION

Removes solid particles that need to be flushed out before they can cause damage to the pump or water heater, for example.

SCOPE OF DELIVERY

With flanged or welded connections on request

TECHNICAL DATA

Maximum operating pressure: 10.0 bar.

Maximum operating temperature: 120 °C.

Minimum temperature: -10°C

Max % glycol: 50%

Maximum recommended flow velocity: 1.5 m/s.

Materials used: Welded steel body EN/ISO S235JRG2, equal to ASTM A181 class 60.

Wall thickness: >10 mm.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

External coating: 2 part Epoxy (RAL 3002), > 45µm.

APPROVALS

CE 0045 in according with PED 97/23/EC.

Codice	Nome	Peso	Numero di pezzi
28188	DN 50	13.94	1
28190	DN 80	23.78	1
28191	DN 100	26.18	1
28192	DN 125	81.6	1
28193	DN 150	86	1
28194	DN 200	123	1
28189	DN 65	14.94	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com