

FLEXVENT



APPLICATION

The compact, proven design has high efficiency and guaranteed operation for heating and air conditioning.

SCOPE OF DELIVERY

The water within the installation contains air which can form corrosion and reduce the thermal transfer. A Flexvent is fitted at places where the air collects. Float operated, the air is collected in the Flexvent causing the float to drop and open the air release valve. When the air is eliminated the float rises and closes the valve.

TECHNICAL DATA

Material: brass

Shut-off valve: yes

Anti leaking system: yes

Min./max. operating temperature: - 10 °C / 90 °C (peak load: 120 °C).

Min./max. operating pressure: 0.2 / 6.0 bar (peak load: 10.0 bar).

Suitable for water and water/glycol solutions up to 50% glycol.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
27735	Flexvent 3/4"	0.16	50
27740	Flexvent 1/2"	0.12	50
27750	Flexvent 3/8"	0.11	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com