

FLAMCO CLEAN SMART PN10



TECHNICAL SPECIFICATIONS

With flanged connection according to EN 1092-1 PN16. Maximum working pressure: 10 bar. Models with a Maximum working pressure of 25 bar are available upon request. Suitable for systems with a maximum flow temperature of 120 °C. Suitable for glycol solutions of up to 50%. In accordance with Pressure Equipment Directive 2014/68/EU.

DN	Capacity [L]	Ø [mm]	A [mm]	B [mm]	C [mm]	D [mm]	Kv * [m ³ /h] (delta P = 1 bar)
50	8	60,3	452	350	129	175	93
65	8	76,1	452	350	129	175	140
80	25	88,9	592	470	172	270	209
100	25	114,3	592	470	172	240	311
125	59	139,7	719	635	219	360	459
150	60	168,3	719	635	224	360	675
200	123	219,1	951	774	361	450	1340
250	287	273	1272	990	395	600	1952
300	333	323,9	1437	1006	420	600	2830
350	646	355,6	1581	1214	487	800	4084
400	731	406,4	1754	1220	517	800	5866
500	1384	508	2081	1580	627	1000	8387

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

DN	CapacitY [L]	Ø [mm]	A [mm]	B [mm]	C [mm]	D [mm]	Kv * [m3/h] (delta P = 1 bar)
600	2390	610	2477	1870	785	1200	11939

Codice	Nome	Peso	Numero di pezzi
31021	DN 50	14	1
31022	DN 65	16	1
31025	DN 100	29	1
31026	DN 125	48	1
31027	DN 150	52	1
31028	DN 200	80	1
31029	DN 250	158	1
31030	DN 300	184	1
31031	DN 350	321	1
31032	DN 400	348	1
31034	DN 600	963	1
31033	DN 500	635	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com