


TEE FITTINGS 130



APPLICATION

Tee fitting short radius for grooved pipe steel

TECHNICAL DATA

Working pressure: 20 bar up to 8".

Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.

Surface treatment: hot galvanized.

NB	ext. Ø [in]	ext. Ø [mm]	L [mm]
50	2"	60,3	70
65	2" 1/2	76,1	76
80	3"	88,9	86
100	4"	114,3	98
125	5"	139,7	110
150	6"	168,3	140
200	8"	219,1	

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

250	10"	273	
300	12"	323,9	

APPROVAL

FM, UL.



Codice	Nome	Peso	Numero di pezzi
130P034Z	48,3 mm 1"½	0.39	72
130P048Z	48,3 mm 1"½	0.76	34
130P060Z	60,3 mm 2"	1.4	30
130P076Z	76,1 mm 2"½	1.83	20
130P089Z	88,9 mm 3"	2.27	12
130P114Z	114,3 mm 4"	3.62	6
130P139Z		6.3	4
130P168Z	168,3 mm 6"	8.71	2
130P219Z	219,1 mm 8"	16.45	1
130P273Z	219,1 mm 8"	27.1	1
130P324Z	219,1 mm 8"	27.1	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com