GASKET FOR COUPLINGS MOD. 270



APPLICATION

Replacement gasket for couplings. Please ask the technical office for not mentioned applications.

TECHNICAL DATA

Grade	Temp. min [°]	Temp. max [°]	Material	Color	Applications
E	-34	+110	EPDM	Green	Potable water, dilute acids, alkalis, salts, and many chemical applications in the absence of hydrocarbons
T	-20	+80	BUNA-N	Orange	Petroleum products, vegetable and mineral oils, air contaminated with mineral oil. Do not use hot water (not over 66 ° C)
L	-34	+177	SILICON	Red	Air dry and warm, hydrocarbon-free and chemical applications at high temperatures.

Codice	Nome	Peso	Numero di pezzi
EPDM042	42,4 mm EPDM	0.1	10
EPDM048	48,3 mm EPDM	0.1	10
EPDM060	60,3 mm EPDM	0.1	10
EPDM076	76,1 mm EPDM	0.1	10
EPDM089	88,9 mm EPDM	0.1	5
EPDM114	114,3 mm EPDM	0.1	5
EPDM139	139,7 mm EPDM	0.1	5
EPDM168	168,3 mm EPDM	0.1	2
EPDM219	219,1 mm EPDM	0.1	1
EPDM273	273,0 mm EPDM	0.1	1
EPDM324	323,9 mm EPDM	0.1	1
BUNA042	42,4 mm Nitrile	0.1	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
BUNA048	48,3 mm Nitrile	0.1	1
BUNA060	60,3 mm Nitrile	0.1	1
BUNA076	76,1 mm Nitrile	0.1	1
BUNA089		0.1	1
BUNA114		0.1	1
BUNA139	139,7 mm Nitrile	0.1	1
BUNA168	168,3 mm Nitrile	0.1	1
BUNA219	219,1 mm Nitrile	0.1	1
BUNA273	273,0 mm Nitrile	0.1	1
BUNA324	323,9 mm Nitrile	0.1	1