BALL VALVE MOD. VSS



APPLICATION

Full bore ball valve for water and fluids with connections for grooved pipe from DN 40 to DN 100. Manual operation with lever. Only size DN40 is ready to connect actuator ISO 5211 and DIN 3337.

TECHNICAL DATA

Connection: grooved
Operation: 90 ° rotation of the control member.
Nominal pressure: PN 25.
Working temperature: from - 20°C to + 160°C.
Flow direction: in both directions.
Pressure drop: see Kv in the table.

TypeDN	A[mm]	B[mm]	C[mm]	D[mm]	E[mm]	Kv[mc/h]
40	114	97	160	48	45	230
50	134.8	90	141.5	60.4	57.1	224.2
65	156.3	116.9	201.5	76.1	72.1	330.2
80	174.4	131.8	281.0	89.5	84.9	419.4
100	177	144	250	114	110	1390

Codice	Nome	Peso	Numero di pezzi
VSS048	48,3 mm 1"½	1.4	1
VSS060	60,3 mm 2"	2.01	1
VSS076	76,1 mm 2"½	3.44	1
VSS089	88,9 mm 3"	5.51	1

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com