
Y-STRAINER MOD. FILTER Y





APPLICATION

Y strainer for vertical or horizontal installation. Grooved connection.

TECHNICAL DATA

Worinkg pressure PN16
Working temperature: - 10°C + 110°C
Basket Hole diameters
Size 2" to 5" hole Ø1,6 mm, free flow area 33%
Size 6" to 8" hole Ø3,0 mm, free flow area 40%.

CARATTERISTICHE COSTRUTTIVE

Body EN -JS1050, ASTM A536 65-45-12
Cover EN-JS1050, ASTM 536 65-45-12
Plug EN-JS1050, ASTM A536 65-45-12
Gasket Teflon/graphite
Red painted

Ø D	H [mm]	L [mm]	Plug
60,3 mm	175	225	½''
76,1 mm	215	285	1''
88,9 mm	219	318	1''
114,3 mm	254	375	1''½
139,7 mm	322	448	2''
168,3 mm	365	502	2''
219,1 mm	462	640	2''

Codice	Nome	Peso	Numero di pezzi
FY060	60,3 mm 2''	4.2	1

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
FY076		7.6	1
FY089	88,9 mm 3"	9.7	1
FY114		12	1
FY139		22	1
FY168	168,3 mm 6"	32.7	1
FY219		55	1
GFY060	60,3 mm 2"	0.05	-
GFY076	76,1 mm 2"½	0.05	-
GFY089	88,9 mm 3"	0.05	-
GFY114	114,3 mm 4"	0.05	-
GFY139	139,7 mm 5"	0.05	-
GFY168	168,3 mm 6"	0.05	-
GFY219	219,1 mm 8"	0.05	-