


FLANGE ADAPTOR MOD. 2278 PN 16



APPLICATION

Grooved flange PN 16.

TECHNICAL DATA

Working pressure: 16 bar

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.
- Surface treatment: red painted RAL 3000.

Type[DN]	Ø est. pipe[pollici]	Ø est. pipe[mm]	Nr. holes	Ø holes [mm]	Do [mm]	L [mm]
50	2"	60,3	4	18	125	65
65	2" 1/2	76,1	4	18	145	65
80	3"	88,9	8	18	160	65
100	4"	114,3	8	18	180	70
125	5"	139,7	8	18	210	70
150	6"	168,3	8	22	240	70

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

200	8"	219,1	12	22	295	80
250	10"	273	12	25	335	85
300	12"	323,9	12	25	410	90

APPROVALS

FM, UL, CE and drinking water certified



Codice	Nome	Peso	Numero di pezzi
2278PN16060	60,3 mm 2"	2	20
2278PN16076	76,1 mm 2"½	1.58	16
2278PN16089	88,9 mm 3"	2.55	15
2278PN16114	114,3 mm 4"	2.44	9
2278PN16139	139,7 mm 5"	5.17	7
2278PN16168	168,3 mm 6"	6.85	6
2278PN16219	219,1 mm 8"	10.25	2
2278PN16273	273,0 mm 10"	15.5	2
2278PN16324	323,9 mm 12"	22.16	2

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com