END CAP WITH ECCENTIRC HOLE 300R



APPLICATION

Closing cap for a pipe, to connect with a grooved joint. With threated eccentric hole.

TECHNICAL DATA

Working pressure: 20 bar up to 8”, 12 bar from 10”

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.
- Surface treatment: hot galvanized.

Type [DN]	Diam. G [inch]	Diam. G [mm]	C [mm]	B [mm]
50	1" 1/2	48,3	7	25
65	2"	60,3	3	25
80	2"	60,3	9	25
100	2"	60,3	22	25
125	2"	60,3	34	25
150	2"	60,3	48	25
200	2"	60,3	73	31

APPROVAL

FM, UL.

Codice	Nome	Peso	Numero di pezzi
300R060048Z		0.43	120

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
300R076060Z	76,1× 60,3 mm 2"½×2"	0.59	75
300R114060Z	114,3× 60,3 mm 4"×2"	1.27	32
300R139060Z	139,7× 60,3 mm 5"×2"	1.79	18
300R168060Z	168,3× 60,3 mm 6"×2"	2.4	12
300R219060Z	219,1x 60,3 mm	5.6	6