
GROOVED BUTTERFLY VALVE W.HANDWHEEL





APPLICATION

Full bore ball valve for water and fluids with connections for grooved pipe. Manual operation with wheel. Ready to attack actuator ISO 5211 and DIN 3337.

TECHNICAL DATA

Connection: grooved
Operation: 90 ° rotation of the control member.
Nominal pressure: PN 25.
Working temperature: from - 20°C to + 160°C.
Flow direction: in both directions.
Pressure drop: see Kv in the table.

NB	Ø [inches]	A [mm]	B [mm]	ØC [mm]	ØD [mm]
50	2"	177	84	90	60,3
65	2" 1/2	197	97	90	76,1
80	3"	207	97	90	88,9
100	4"	255	116	90	114,3
125	5"	261	148	90	139,7
150	6"	328	148	90	168,3
200	8"	381	133	125	219,1

Material:
- Body: brass CW617N
- Ball: brass CW614N
- Seat ting, packing: P.T.F.E.
- O-ring: NBR 70Sh.
- Washer, ratchet, screw, reatainer, nut: steel.

Warnings
We recommend the use of the valve in fully open or closed, not in mid. Operate at least twice a year.

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVAL

EN 593.

Codice	Nome	Peso	Numero di pezzi
VSV-219	219,1 mm 8"	23	-
VSV-273	273,0 mm 10"	32	-
VSV-324	323,9 mm 12"	37	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com