
UGELLO GETTO PIATTO A LAMA D'ACQUA



APPLICATION

Create a horizontal or veticale jet as a fire wall. The flow change in according to the exit hole. To be installed in vertical or horizontal position.

NOTES FOR PROJECT PLANNING

For the design of this type of nozzle, the UNI 12845 is not expressed. For a indication of the size of these systems we refer to NFPA 13 (11.3.3 "Water curtains"), which decrees that the in a sprinkler the flat jet nozzles must ensure a flow of 37 l / min per linear meter; in the absence of sprinkler system,must be guaranteed a flow of 56.8 L / min.

TECHNICAL DATA

Characteristics: Nozzle with blade water.

Attack: 1/2 "

Spray angle: 140°

Material: Brass.

Codice	Nome	Peso	Numero di pezzi
131240	1/2'' K5	0.2	10
131241	1/2'' K7	0.2	10
131242	1/2'' K9	0.2	10
131243	1/2'' K11	0.2	10
131244	1/2'' K16	0.2	10
131245	1/2'' K18	0.2	10
131246	1/2'' K22	0.2	10
131247	1/2'' K27	0.2	10
131248	1/2'' K31	0.2	10
131249	1/2'' K41	0.2	10
131250	1/2'' K52	0.2	10

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
131251	1/2'' K63	0.2	10
131252	1/2'' K95	0.2	10