SPRINKLER UPRIGHT - STANDARD RESPONSE - RTI > 80



APPLICATION

Sprinkler pendent, made of brass, with a sensitivity of standard response,threaded connection 1/2 "and 3/4" K-factor 80 or 115 with 5mm glass bulb. Made for the jet directed downwards against the deflector.

Not to be used for dry systems.

TECHNICAL DATA

Characteristics: spray sprinkler, pendent

Response sensitivity: standard RTI >80

Max working pressure: 12,0

Min request pressure: 0,68 bar

k factor:80;115

Material:

- Sprinkler body: brass (on request chrome-plated version);
- Deflector: brass (on request stainless steel version);
- Glass bulb: borosilicate glass;
- Threaded pin: brass.

APPROVALS

1/2” version: certified CE and FM.

3/4” version: certified CE.

Codice	Nome	Peso	Numero di pezzi
843090	1/2'' K80 57 °C	0.06	50
843091	1/2'' K80 68 °C	0.06	50
843092	1/2'' K80 79 °C	0.06	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
843093	1/2'' K80 93 °C	0.06	50
843094	1/2'' K80 141°C	0.06	50
843100	3/4'' K115 57 °C	0.06	50
843101	3/4'' K115 68 °C	0.06	50
843102	3/4'' K115 79 °C	0.06	50
843103	3/4'' K115 93 °C	0.06	50
843104	3/4'' K115 141°C	0.06	50