SPRINKLER RETRACTABLE - RTI < 50



APPLICATION

Pendent sprinkler, made of brass, with a sensitivity of fast response, threaded pin of 1/2 "and 3/4" K-factor 80 or 115 with glass bulb. Particularly suitable in environments where it is necessary to hide the fire protection system. Made for the jet directed downwards against the deflector. Not to be used for dry systems.

TECHNICAL DATA

Characteristics: spray sprinkler, pendent

Response sensitivity: RTI<50

Max working pressure: 12,5 bar

Min request pressure: 0,35 bar

k factor:80

Release temperature:

- Sprinkler:68°C and 93°C

- Protective escutcheon: 58°C and 79°C

- Area covered: 12m2

Material:

- Sprinkler: chrome-plated brass;

- Deflector: stainless steel;

- Glass bulb: borosilicate glass;

- Threaded pin: brass;

- Seal: teflon;

- Protective plate: Chromed steel (C) or with RAL 9010 white powder (B) type equipped with magnetic sensing element for the posting.

Warning: Obligation mounting wrench.

APPROVALS

Vds and CE certification.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
845911	1/2'' K80 Bianco 68°C	0.15	50
845917	1/2'' K80	0.15	50
845918	1/2'' K80	0.15	50
845920	piattello	0.1	50
845921	piattello	0.15	50
845930	chiave	0.21	50

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com