FLANGED SHUTTER VALVE NRS PN16



APPLICATION

Internal screw flanged damper (NRS) with handwheel. Suitable for horizontal or vertical installation, equipped with open/close indicator.

TECHNICAL DATA

Connections: Flanged DIN-EN 1092-2 PN16
Operating temperature: 0°C to +80°C
Surface coating: red epoxy paint RAL 3000

n	Description	Material
1	Valve body	Ductile iron
2	Disk	Ductile iron+ EPDM
3	Lid	Ductile iron
4	Gland	Ductile iron
5	Stem	Stainless steel
6	Wheel	Ductile iron
7	Indicator	Stainless steel

Type		Dimensions		
Ø	mm	L	H	M
2"	DN 50	150	282	180
2 ½"	DN 65	170	290	180
3"	DN 80	180	331	200
4"	DN 100	190	366	254
5"	DN 125	200	447	280
6"	DN 150	210	490	305
8"	DN 200	230	560	350
10"	DN 250	250	706	450
12"	DN 300	270	802	450

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVALS

FM, UL, CE, Ghost.

Codice	Nome	Peso	Numero di pezzi
849704	DN 50	10.3	1
849705	DN 65	12.3	1
849706	DN 80	16.3	1
849707	DN 100	21.1	1
849709	DN 150	42.3	1
849711	DN 200	57.3	1
849713	DN 250	105.5	1
849716	DN 300	169.2	1
849723	Switch	0.3	1