SPRINKLER UPRIGHT - QUICK RESPONSE - RTI > 50



APPLICATION

Sprinkler pendent,made of brass, fast response,threaded connection 1/2 "and 3/4" K-factor 80 or 115 with glass bulb. Made for the jet directed downwards against the deflector.

Particularly suitable for dry systems.

TECHNICAL DATA

Characteristics: spray sprinkler, pendent

Response sensitivity: fast RTI<50

Max working pressure: 12,0

Min request pressure: 0,68 bar

k factor:80;115

Material:

- Sprinkler body: brass (on request chrome-plated version)
- Deflector: brass (on request stainless steel version)
- Glass bulb: borosilicate glass
- Threaded pin: brass

APPROVALS

1/2” version: certified CE and FM.

3/4” version: certified CE.

Codice	Nome	Peso	Numero di pezzi
843060	1/2'' K80 57 °C	-	50
843061	1/2'' K80 68 °C	0.06	50
843062	1/2'' K80 79 °C	0.06	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
843063	1/2'' K80 93 °C	-	50
843064	1/2'' K80 141°C	-	50
843070	3/4'' K115 57 °C	-	50
843071	3/4'' K115 68 °C	0.06	50
843072	3/4'' K115 79 °C	-	50
843073	3/4'' K115 93 °C	-	50
843074	3/4'' K115 141°C	-	50